



# David GNSS Receiver

## Overview

---

The Tersus David is a cost-efficient, palm-sized GNSS receiver designed for surveying, UAVs, AGVs, and agricultural applications. Working with an external GNSS antenna, the free Tersus Survey App and post-processing software, the David GNSS receiver is a low-cost solution for all survey applications, including real-time RTK positioning and data collection for PPK.

A 4GB in-built memory makes it easy to record data for post processing. The compact size, IP67-rated enclosure, and external Bluetooth module alleviates most of the inconveniences encountered in field work.

## Key Features

---

Supports GPS L1/L2, GLONASS L1/L2, and BeiDou B1/B2

---

Supports RTCM2.3/3.x, CMR, CMR+ corrections

---

Easy to connect an external powerful radio for long range

---

Solution update rate up to 10Hz

---

20Hz raw measurement output for post processing

---

The carrier phase accuracy down to 1mm

---

Post-processing software for 1cm-level positioning accuracy

---

Input power range is 5-12V, connect to battery bank directly

---

IP67-rated dust- & waterproof enclosure, for reliability in harsh environmental conditions

---





# Technical Specifications

## Performance

Frequencies For Antenna:	
GPS L1/L2, GLONASS L1/L2, BeiDou B1/B2	
Single Point Positioning Accuracy (RMS):	
– Horizontal:	1.5m
– Vertical:	3.0m
Real Time Kinematic (RMS):	
– Horizontal:	10mm+1ppm
– Vertical:	15mm+1ppm
Post Processed Kinematic (RMS):	
– Horizontal:	10mm+1ppm
– Vertical:	15mm+1ppm
Static Post Processing (RMS):	
– Horizontal:	3mm+0.5ppm
– Vertical:	5mm+0.5ppm
Observation Accuracy:	
– C/A Code (zenith direction):	10cm
– P Code (zenith direction):	10cm
– Carrier Phase (zenith direction):	1mm
Time To First Fix (TTFF):	
– Cold Start:	<50s
– Warm Start:	<30s
Timing Accuracy (RMS):	20ns
Velocity Accuracy (RMS):	0.03m/s
Initialization (typical):	<10s
Initialization Reliability:	>99.9%
Max. Measurements Update Rate:	20Hz

## Communication

Serial Ports:	RS232+TTL
USB Ports:	USB 2.0 device x1

## Physical

Input Voltage:	5V~12V DC
Power Consumption:	3.2W (David only)
Active Antenna Input Impedance:	50Ω
Size:	104x65x31mm (David only)
Weight:	250g (David only)
Antenna Connector:	SMA female x1
COM Baud Rate:	Up to 921600bps
Operating Temperature:	-40°C ~ +85°C
Dust- & Waterproof:	IP67

## Optional Accessories

1W 915MHz/2W 460MHz/30W 460MHz radio to transmit/receive RTK corrections
Battery bank

