

Tersus TC40 Controller



Overview

The Tersus TC40 Controller is a rugged smart phone with design of 8" IPS screen and 1280*800 resolution.

Equipped with Android 8.1 mainstream operating system, 8-core 2.0G processor, it is perfect to adapt with Tersus Survey software and run fastly. The 9000mAh large capacity battery is detachable, which can work continuously for 10 hours without pressure. The unique rounded corner design and plastic shell are compatible with appearance and protection. With professional IP67 rating, it is robust and reliable for harsh operating conditions.

Key Features

8" IPS screen, 1280*800 resolution

Android 8.1 operating system

8-Core 2.0GHz CPU

4GB RAM + 64GB ROM

Front 5 Million Fixed Focus, Rear 13 million auto focus camera

IP67 certified grade, water/shock/dust proof

9000mAh battery

Wi-Fi, Bluetooth, NFC

Supports GPS,BDS & GLONASS

Unique rounded corner design & plastic shell



Technical Specifications

System

Operating System:	Android 8.1
CPU:	8-Core 2.0GHz
Memory:	4GB RAM + 64GB ROM
Camera:	Rear 13 Million AutoFocus; High-Brightness LED Flash; Front 5 Million Fixed Focus
Display:	8" IPS Screen
Resolution:	1280x800
Touch Screen:	5-point Capacitive Touch Screen
External Interface:	20 pin Pogo Extended Port, used for Fingerprint Mouldle; 6 pin Pogo Port ,used to connect Charger
External Storage:	Micro SD*1, Up to 128GB
Keypad :	6 Physical Buttons, 1 Power Button
Earphone:	3.5mm Earphone Jack
Audio:	Rear Stereo Speakers, Volume 90db±3db (Test Distance 10cm)
Notification Method:	Sound, Vibratation, LED Prompt
Fingerprint Moudle:	TCS1G Reserved

Barcode Scanning Support Code System:
AZTEC、CODABAR、CODE11、CODE128、EAN128、
CODE39、CODE49、CODE93、COMPOSITE、
DATAMATRIX、EAN8、EAN13、INT25、MAXICODE、
MICROPDF、PDF417、POSTNET、OCR、QR、RSS、
UPCA、UPCE、ISBT、BPO、CANPOST、AUSPOST、
IATA25、CODABLOCK、JAPOST、PLANET、
DUTCHPOST、MSI、TLC39、TRIOPTIC、CODE32、
STRT25、

GNSS

Signal Tracking:	GPS, BDS, GLONASS
------------------	-------------------

Communication

Wi-Fi:	IEEE 802.11a/b/g/n 2.4G 5G Double Frequency
Cellular Mode:	Dual SIM Dual Standby
SIM1 & SIM2:	FDD-LTE B1/B3/B7/B8 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA1 _x /CDMA2000 BC0/BC1
Bluetooth:	BT4.1 & BLE
RFID(High Frequency)	
Support Agreement:	ISO14443A/B, ISO15693
NFC Reading Distance:	0~5cm
Sensors:	Gravity Acceleration Sensor Geomagnetic Sensor, Light and Distance Sensor

Electrical

Battery:	9000mAh
Working Time(Typical):	≥10 Hours
Charging Ways:	USB TYPE-C Fast Charge 5V/9V 1.5A

Physical

Dimension:	234mmx150mmx19.6mm
Weight:	700g (Include Battery)
Operating Temperature:	-20 °C ~ +55 °C
Storage Temperature:	-30 °C ~ +70 °C
Operating Humidity:	5% ~ 95%
Dustproof & Waterproof:	IP67
Shock:	1m Drop Onto Concrete(6 Sides)
Electrostatic Protection:	±15kV Air Discharge; ±8kV Contact Discharge

Website | www.tersus-gnss.com
Sales Inquiry | sales@tersus-gnss.com
Technical Support | support@tersus-gnss.com

