

Tersus TC40 Controller



Overview

The Tersus TC40 Controller is a rugged smart phone with design of 8" IPS screen and 1280*800 resolution.

Equipped with Android 8.1 mainstream operating system, 8-core 2.0G processor, it is perfect to adapt with Tersus Survey software and run fastly. The 9000mAh large capacity battery is detachable, which can work continuously for 15 hours without pressure. The unique rounded corner design and plastic shell are compatible with appearance and protection. With professional IP67 rating, it is robust and reliable for harsh operating conditions.

Key Features

8" IPS screen, 1280*800 resolution

Android 8.1 operating system

8-Core 2.0GHz CPU

4GB RAM + 64GB ROM

Front 5 megapixels fixed focus,
Rear 13 megapixels auto focus camera

IP67 certified grade, water/shock/dust proof

9000mAh battery

Wi-Fi, Bluetooth, NFC

Supports GPS,BDS,GLONASS & Galileo

Unique rounded corner design & plastic shell



Technical Specifications

System

Operating System:	Android 8.1
CPU:	8-Core 2.0GHz
Memory:	4GB RAM + 64GB ROM
Camera:	Rear 13 Megapixels AutoFocus; High-Brightness LED Flash; Front 5 Megapixels Fixed Focus
Display:	8" IPS Screen
Resolution:	1280x800
Touch Screen:	5-point Capacitive Touch Screen
External Interface:	20 pin Pogo Extended Port, used for Fingerprint Moudle; 6 pin Pogo Port ,used to connect Charger
External Storage:	Micro SD*1, Up to 128GB
Keypad :	6 Physical Buttons, 1 Power Button
Earphone:	3.5mm Earphone Jack
Audio:	Rear Stereo Speakers, Volume 90db±3db (Test Distance 10cm)
Notification Method:	Sound, Vibrtation, LED Prompt
Fingerprint Moudle:	TCS1G Reserved
Barcode Scanning Support Code System:	EAN13, EAN8, UPCA, UPCE, Code 128, Code 39, Codabar, UCC/EAN128,RSS, ITF, ITF14, ITF6 , IS SN, ISBN, Standard 25,AZTEC,Matrix 25,Industrial 25, Plessey, MSI Plessey, Code 11, Code 93,PDF417, QR Code, DataMatrix,Hanxin code , Maxicode, Micro QR, Micro PDF417, Composite

GNSS

Signal Tracking:	GPS, BDS,GLONASS,GALILEO
------------------	--------------------------

Communication

Wi-Fi:	IEEE 802.11a/b/g/n 2.4G 5G Double Frequency
Cellular:	Minimum 4G LTE cellular modem
Cellular Mode:	Dual SIM Dual Standby(4G&5G)
SIM1 & SIM2:	FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 GSM 850/900/1800/1900MHz CDMA1 _x /CDMA2000 BC0/BC1
Bluetooth:	BT4.1 & BLE
RFID(High Frequency)	
Support Agreement:	ISO14443A/B, ISO15693
NFC Reading Distance:	0~5cm
Sensors:	Gravity Acceleration Sensor Geomagnetic Sensor,Light and Distance Sensor

Electrical

Battery:	9000mAh
Working Time(Typical):	15 Hours
Charging Ways:	USB TYPE-C Fast Charge 5V/9V 1.5A

Physical

Dimension:	235mmx150mmx17.6mm
Weight:	700g (Include Battery)
Operating Temperature:	-20 °C ~ +60 °C
Storage Temperature:	-30 °C ~ +70 °C
Operating Humidity:	5% ~ 95%
IP67 dust tight and withstands temporarily immersion under water	
Shock:	1.2m Drop Onto Concrete(6 Sides)
Electrostatic Protection:	±15kV Air Discharge; ±8kV Contact Discharge

https://www.tersus-gnss.com/product/TC40_controller-with-options

Website | www.tersus-gnss.com
Sales Inquiry | sales@tersus-gnss.com
Technical Support | support@tersus-gnss.com

