

Tersus GNSS

Oscar ProBase GNSS Receiver

Overview

The Oscar ProBase GNSS receiver is the new generation of Tersus's super base station system. The built-in UHF radio module supports long-distance communication and can be easily carried without an external radio. The dual transmitter for radio and network can easily be configured with a 1.54" interactive screen. The Oscar ProBase GNSS receiver can provide high accuracy and stable signal detection with an internal high-performance multi-constellation and multi-frequency GNSS board. The high-performance antenna can speed up the time to first fix (TTFF) and improve anti-jamming performance. The built-in large-capacity battery is detachable, and two batteries support up to 14 hours of fieldwork in Base 5W radio mode. The rugged housing protects the equipment from challenging environments.

Key Features

- ✓ Supports multiple constellations and frequencies
 - GPS L1, L2, L5
 - GLONASS L1, L2
 - BeiDou B1I, B2I, B3I, B1C, B2a
 - Galileo E1, E5a, E5b
 - QZSS L1, L2, L5
- ✓ Supports 1000 channels
- ✓ Built-in 5W radio to support long-distance operation
- ✓ 8GB internal storage
- ✓ Up to 14 hours working in Base 5W radio mode
- ✓ IP68-rated dust- & waterproof enclosure for reliability in challenging environmental conditions
- ✓ Free subscription to Tersus Caster Service (TCS): transmit the correction data from Base to Rover



Tersus GNSS

Oscar ProBase GNSS Receiver

Technical Specifications

Performance

Signal Tracking:	
GPS: L1, L2, L5	
GLONASS: L1, L2	
BDS: B1I, B2I, B3I, B1C, B2a	
Galileo: E1, E5a, E5b	
QZSS: L1, L2, L5	
Channels:	1000
Single Point Positioning Accuracy (RMS):	
- Horizontal:	1.5m
- Vertical :	2.5m
DGPS Positioning Accuracy (RMS):	
- Horizontal:	0.25m
- Vertical:	0.5m
High-Precision Static (RMS):	
- Horizontal:	2.5mm+0.1ppm
- Vertical:	3.5mm+0.4ppm
Static & Fast Static (RMS):	
- Horizontal:	2.5mm+0.5ppm
- Vertical:	5mm+0.5ppm
Post Processed Kinematic (RMS):	
- Horizontal:	2.5mm+1ppm
- Vertical:	5mm+1ppm
Real Time Kinematic (RMS):	
- Horizontal:	8mm+1ppm
- Vertical:	15mm+1ppm
Initialization (Typical):	4s ⁽¹⁾
Initialization Reliability:	>99.9% ⁽²⁾
Network Real Time Kinematic (RMS):	
- Horizontal:	8mm+0.5ppm
- Vertical:	15mm+0.5ppm
Observation Accuracy (zenith direction):	
- C/A Code:	10cm
- P Code:	10cm
- Carrier Phase:	1mm

Timing Accuracy (RMS):	20ns
Velocity Accuracy (RMS):	0.03m/s
Time To First Fix (TTFF):	
- ColdStart:	<30s
- WarmStart:	<5s
Re-acquisition:	<1s

System & Data

Operating System:	Linux
Storage:	Built-in 8GB
Differential Data Format:	CMR, RTCM2.x, RTCM3.x
Data Output:	RINEX, NMEA-0183, Tersus binary
Data Update Rate:	20Hz

Software Support

Tersus Nuwa

Communication

Cellular:	4G LTE/WCDMA/GSM
Cellular Bands ⁽³⁾ :	
	FDD LTE 1,3,7,8,20,28A 2,4,5,12,13 TDD LTE 38,40,41 WCDMA 1,8 2,5 GSM3,8
Network Protocols:	Ntrip Client, Ntrip Server, TCP, Tersus Caster Service (TCS)
Wi-Fi:	802.11b/g
Bluetooth:	4.1
NFC:	Support
Internal Radio	
RF Transmit Power:	1W/2W/5W
Frequency Range:	410MHz ~ 470MHz
Operating Mode:	Half-duplex
Channel Spacing:	25KHz

Technical Specifications

Modulation Type:	GMSK
Air Baud Rate:	9600 / 19200bps
Distance (Typical):	>8km
Radio Protocols:	TrimTalk450, TrimMark 3, South, Transparent, Satel

Wired Communication

USB OTG:	USB 2.0 x1
Serial Ports:	RS232 x1
COM Baud Rate:	up to 921600bps

Electrical

Input Voltage:	9~28V DC
Power Consumption (Typical):	
Network or Radio Receive Mode:	≈ 5W
Radio Transmit Mode (1W):	≈ 8W
Radio Transmit Mode (2W):	≈ 9W
Radio Transmit Mode (5W):	≈ 11W
Lithium Battery:	7.4V 6400mAh x2 ⁽⁴⁾
Battery Charging Temperature:	+10°C ~ +45°C
Battery Working Time:	up to 14 hours ⁽⁴⁾
Smart Battery with Power Display:	Support
Electronic Bubble:	Support

Physical

Display:	1.54" OLED
Buttons:	FN, ON/OFF
LED Indicators:	Satellite, Static, Correction data, Power
Dimension:	157x157x103mm ⁽⁵⁾
Weight:	≈ 1.2kg (without battery) ≈ 1.4kg (with a battery) ⁽⁵⁾
Operating Temperature:	-40°C ~ +70°C
Storage Temperature:	-55°C ~ +85°C
Relative Humidity:	100% not condensed
Dust- & Waterproof:	IP68
Pole Drop onto Concrete:	2m
Vibration:	MIL-STD-810G, FIG 514.6C-1
Warranty period:	ONE Year

Note:

- (1) The initialization time depends on various factors, including the number of satellites, observation time, atmospheric conditions, multi-path, obstructions, satellite geometry, etc.
- (2) The initialization reliability may be affected by atmospheric conditions, signal multipath, and satellite geometry.
- (3) Depending on version. In order Europe | American version.
- (4) Oscar ProBase uses one battery at a time, the other is a substitute. Each battery lasts up to 7 hours when OscarProBase works in Base 5W radio mode. Two batteries add up to 14 hours of continuous use. The working time of the battery is related to the working environment, working temperature and battery life.
- (5) The actual size/weight may vary depending on the manufacturing process and measurement method.

Website: www.tersus-gnss.com
Sales Inquiry: sales@tersus-gnss.com
Technical Support: support@tersus-gnss.com

Information is subject to change without notice.
© Copyright 2024 Tersus GNSS Inc.